

PRODUCT SPEC SHEET

OMNII XT15 For Oracle



OMNII XT15 For Oracle

ADAPTABILITY GIVES YOU MORE

The Omnii[®] XT15 is uniquely adaptive by design ' combining extreme versatility with open innovation to deliver the flexibility you require to adapt as your business needs change. As the next evolution of the Omnii platform, the Omnii XT15 takes the best features of the Omnii XT10 and adds new functionality to create a device that gives mobile workers the greatest access to business applications ' anytime, anywhere.

Working with our customers and partners who specialize in mobile computing solutions for Oracle, Zebra has developed a custom version of our modular Omnii device especially for the Oracle user. Taking into account the functions that an Oracle Mobile Supply Chain Applications (MSCA) user needs most while operating a mobile computer, Zebra has added unique keyboard functionality to our Omnii for Oracle device.

FEATURES AND BENEFITS

Adaptive by Design

Tested and developed with our customers and partners, Omnii XT15 is uniquely adaptive by design. So you can quickly configure it to meet virtually any business need. Omnii XT15 is a product of Zebra's open source business model, a single, versatile computing platform that gives you the flexibility and freedom to adapt your device with exactly what you need ' when you need it. Adding new technologies as required with minimal cost and no risk of obsolescence.

Omnii for Oracle MSCA

Zebra has taken the most commonly used action keys and created a keyboard that simplifies navigation for Oracle MSCA users. With Omnii for Oracle, multiple commands are accessed by function keys and control action buttons. All key mapping is done in the background, thus creating a meaningful key sequence for the end user. By creating these ' Hot ' action keys and by grouping them in one single location on the Omnii for Oracle keyboard, users can increase transaction speed, reduce training times, and improve overall efficiency.

Technology Made Tough

The Omnii XT15 comes with the option of Windows[®] CE 6.0 or Windows[®] Embedded Handheld 6.5 operating systems, both of which integrate seamlessly to automate key processes and boost productivity in real-time. Plus, it is certified IP67 and IP65 so it will work wherever you take it.

Field-Upgradeable Adaptability

Omnii[®] XT15 is always fit for purpose, so you can configure it the way you want and later bolt on what you need. This allows for future-proof flexibility as hardware can be reconfigured ' and not replaced ' saving your business up to 30% on lifetime total cost of ownership.

Real-World Practicality

Zebra understands how to make mobile workers more productive in the harshest of environments and we have designed all elements of the Omnii XT15 to reflect that expertise. Built with the Texas Instruments[®] OMAP3

TYPICAL APPLICATIONS

- Oracle Mobile Supply Chain Applications
- Warehousing
- Manufacturing
- Distribution & Logistics

microprocessor and a Zebra designed Custom ASIC architecture, Omnii XT15 delivers industry-leading performance and efficiency with an extended battery life of up to 20 hours. The 3.7" VGA color display allows for improved worker visibility and the 95db keypad beeper with vibration feedback is perfect for loud industrial environments.

Optimized Ergonomics

Ergonomics are crucial to ensuring mobile workers are efficient and effective on their jobs. The Omnii XT15 features a balanced construction that is perfectly weighted for comfort, practicality and Natural Task Support. Furthermore, Omnii XT15 is equipped with PsionVU software and transfective touch screens that enable a friendly user interface.

THE ULTIMATE HANDHELD FOR ORACLE MOBILE SUPPLY CHAIN APPLICATIONS

For more information, please visit www.zebra.com/omniixt15

TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS		PERFORMANCE CHARACTERISTICS	
Flexibility	Customer IT or VAR serviceable; Maximum 'last step' configurability; Keypads*, endcaps, pods swappable	CPU	Texas Instruments® AM3715 Sitara ARM Processor, 800 MHz
Dimensions	8.86 in. L x 3.86 in. W x 1.73 in. D (at display); 1.22 in. D (at grip area) 225 mm L x 98 mm W x 44 mm D (at display); 31 mm D (at grip area)	Operating System	Windows® CE 6.0; Windows® Embedded Handheld 6.5
Weight	1.34 lbs./610 g (basic unit with battery)	Memory	256MB RAM (512MB Option) and 1 GB Flash ROM
Keyboard Options	Omnii for Oracle 59-key full alpha numeric 6Fn keys*; 55-key Alpha Numeric, phone keys; Omnii for Oracle 66-key QWERTY Numeric 6 Fn keys, phone keys*; 36-key Numeric, 12 Fn keys; 36-key Numeric Alpha Modified, 12 Fn keys; 34-key Numeric; High reliability keypad ultra-white backlight *Non-Oracle version also available.	Bar Code Scanner	Zebra SE955 Std Range Laser; Zebra SE1224HP 1-D Std Range Laser; Zebra SE1524ER Auto-Range Laser, Zebra SE4600 1-D/2-D Extended Range Imager
Power	5000 mAh high capacity Lithium Ion smart battery	Application Software	Windows CE 6.0: Internet Explorer Embedded, Microsoft WordPad; Windows Embedded Handheld 6.5 : Windows® Office Mobile 2010, includes Word, Excel, PowerPoint, OneNote and SharePoint; Internet Explorer Mobile; Windows Office Outlook Mobile; Windows Media Player Mobile
Display	3.7" VGA (640 x 480) Transfective Color/Touch Display; 2 Touchscreen options: High Visibility option, Extreme Duty option	Terminal Emulation	Open TekTerm; Stay-Linked Terminal Emulation; Naurtech Browser; Naurtech Terminal Emulation
Audio	Integrated microphone and speaker; high volume 95dBA beeper; optional Push-to-Talk speaker; vibration feedback	Mobile VPN	NetMotion Mobility XE VPN
Voice Applications	Walkie-talkie style Push-to-Talk ' VoIP over WiFi or WWAN	Device Mgmt	Mobile Control Center (MCC)
Camera (optional)	Color, 3 Mega pixel, autofocus, 4X digital zoom, Dual LED flash, Video capable (configurable with	Software Utilities	PsionVU; Total Recall / TweakIt / Dr. Debug
		WIRELESS DATA COMMUNICATIONS	
		WLAN	On-board IEEE 802.11a/b/g/n, (CCX v4) radio; Security: 802.1X, WPA / WPA2- Enterprise & Shared Key, Authentication: FAST-MSCHAPv2;

pistol grip)

LEAP; PEAPv0-MSCHAPv2;
PEAPv1-GTC; TLS;
Encryption: 64/128 WEP,
AESCCMP, TKIPP

USER ENVIRONMENT

Operating Temp. -20°C to +50°C / -4°F to +122°F

Storage Temp. -40°C to +60°C / -40°F to +140°F

Humidity 5% to 95% non-condensing

Sealing IP67, IP65, IEC 60529

Drop Spec Multiple 6.5ft /2 m drops to
polished concrete

Integrated Sensors Motion (accelerometer); digital
compass

ESD +/- 8kV contact, +/- 15kV air
discharge

GPS (optional) SIRF III GPS Receiver

WWAN (optional) 2.5G GSM/GPRS/EDGE radio,
Quad-Band GSM:
850, 900, 1800, 1900 MHz;
UMTS 3.8G HSPA+ radio, Five
Band UMTS:
800/850, 900, 1900, 2100 MHz,
Quad-Band GSM: 850, 900, 1800,
1900 MHz

WPAN Integrated Bluetooth® V2.0 + EDR

WARRANTY

Subject to the terms of Zebra's hardware warranty statement, the Omnii XT15 is warranted against defects in workmanship and materials for a period of 1 (one) year from the date of shipment. For complete warranty statement, go to: <http://www.zebra.com/warranty>

REGULATORY

Worldwide Safety, EMC, RF, Laser approvals; CE Mark; E Mark (vehicle cradles); RoHS compliant; WEEE compliant; REACH compliant

ACCESSORIES

For a complete list of accessories, visit www.zebra.com/omniixt15.

SERVICES AND SUPPORT

- Zebra Primary Services



Part number: SS-OMNIXT15-Oracle. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

ZEBRA TECHNOLOGIES